

**IBIX SPARTACUS
FLAME COATING SYSTEM
ITEM #: I-SP001-G**



STEEL APPLICATION GUNS



**CONCRETE APPLICATION GUN
"CENTURION" GUN**

MAX. OPERATING GAS PRESSURE:	43 PSI = 3 BAR
FUEL GAS:	LIQUID PROPANE GAS
HOSE LENGTH:	30 FT. (10 M)
MAX. GAS FLOW RATE:	SMALL GUN 114 BTUH MEDIUM GUN 172 BTUH LARGE GUN 220 BTUH
TANK CAPACITY:	30 L = 7.93 GAL. -- 40 LBS..
AIR PRESSURE:	87 PSI = 6 BAR
PERFORMANCE:	350—500 SQFT./HR.
MINIMUM AIR:	35 CFM
SYSTEM FEATURES:	3-IN-1-SYSTEM
PACKAGING DIMENSIONS (BOX):	36 x 30 x 56" (IN BOX ON PALLET)
MACHINE GROSS WEIGHT:	245 LBS. (IN BOX ON PALLET)
SURFACE COATING:	ASK FOR OUR POLYMER SELECTION AND COLORS 
APPLIED STANDARDS:	
CGA2.29-1997 (R2014)	HAND-HELD TORCHES FOR FUEL GASES
UL-147	STANDARD FOR HAND HELD TORCHES FOR FUEL GASES