

AIR REQUIREMENTS FOR IBIX SYSTEMS

SMALL RANGE

17-20 CFM
Gas or Electrical
Mi-T-M C-M2-17



	IBIX 3 10-12 CFM		IBIX 9 17-23 CFM
Runs × 2 Units		or	× 1 Unit

These compressors show the maximum number of IBIX systems that can be ran consecutively while successfully achieving maximum, consistent air flow.

MEDIUM RANGE

70 CFM
Gas
Rotair VRK 220



	IBIX 9 17-23 CFM		IBIX 25 57-64 CFM
Runs × 3 Units		or	× 1 Unit

(The use of a dryer is recommended between the compressor and system for moisture control)

MEDIUM RANGE

115 CFM
Gas
Mi-T-M C-PK37-115



	IBIX 9 17-23 CFM		IBIX 25 57-64 CFM
Runs × 6 Units		or	× 2 Units

When using your IBIX System for your surface preparation project, we recommend starting with the lowest pressure setting available. Test patching your surface preparation project is highly recommended to ensure the correct abrasive media has been selected for your surface preparation project.

LARGE RANGE

185 CFM
Diesel
Rotair MDVN 5200








	IBIX 9 17-23 CFM		IBIX 25 57-64 CFM		IBIX 40 177-185 CFM
Runs × 10 Units		or	× 3 Units	or	× 1 Unit

EXTRA LARGE RANGE

375 CFM
Diesel
Rotair MDVS Line



	IBIX 3 10-12 CFM		IBIX 9 17-23 CFM		IBIX 25 57-64 CFM		IBIX 40 177-185 CFM		IBIX 60 185 CFM (1 air line) 283 CFMs (2 air lines)
Runs × 37 Units		or	× 18 Units	or	× 6 Units	or	× 2 Units	or	× 1 Unit